Diamond cup grinding wheel

DS 300 B *EXTRA*





Properties

Design	Brazed
Segmentation	Standard
Aggression	■■■■□□□
Service life	■■■■□□□

Materials

Concrete	●
Screed	●
Construction materials	●

Product benefit

Double row cup grinding wheel with outstanding stock removal performance - High aggressiveness at low force requirements - Exceptional price-performance ratio - M14 adapter available, see DZ 114

Applications

- Building construction
- Floor tilers
- Concrete plants
- Natural stone businesses

Diameter x Bore in mm	Cup grinding wheel height [mm]	Vmax m/s	Max. RPM	Segment in mm: Number / Width / Height	Packing unit/pcs.	Cat. number
100 x 16 / 22,23	20	80 m/s	15300 rpm	14 / 7 / 5,5	1	330622
115 x 22,23	20	80 m/s	13300 rpm	14 / 8,2 / 5,5	1	325361
125 x 22,23	24,5	80 m/s	12200 rpm	18 / 7 / 5	1	325362
180 x 22,23	30,5	80 m/s	8500 rpm	22 / 8 / 5	1	325363

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de