Abrasive screen, self-fastening, waterproof

AN 400





Properties

Bonding agent	Resin
Grain	Aluminium oxide
Backing	Polyester screen

Materials

Paint/Varnish/Filler	●
Gel coats	●
Plaster	●
Plasterboard walls	●
Composite materials	●
Wood	●
Wood-based materials	●

Product benefit

Effective and full-surface dust extraction thanks to open grid structure - Dust-free grinding extends the service life of the abrasive - At the same time, improved health and safety thanks to reduced dust formation at the work station - Independent of existing extraction hole patterns - Waterproof

Available grits:

16 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Width x Length in mm	grain	Packing unit/pcs.	Cat. number
115 x 10000	80	1	348458
115 x 10000	100	1	353063
115 x 10000	120	1	348418
115 x 10000	150	1	349059
115 x 10000	180	1	353062
115 x 10000	240	1	349058

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Width x Length in mm	grain	Packing unit/pcs.	Cat. number
115 x 10000	400	1	353060

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de