End brush with shaft, knotted wire

BPS 600 Z







Product benefit

Tool diameter changes depending on the rotation speed - Perfectly suited for working on pipe inner surfaces or bores - High brushing effect due to knotted wire design

Materials

Steel	●
Stainless steel	●

Applications

- Plant engineering
- Apparatus and container manufacturing
- Stainless steel processing industry
- Railing construction
- Metal construction
- Steel construction
- Locksmith's shop

Diameter x Shaft in mm	Total length in mm	Fill material	Wire thickness in mm	Fill length in mm	Number of knots	Max. RPM	Packing unit/pcs.	Cat. number
19 x 6	70	Steel	0,35	25	6	20000 rpm	20	358333
19 x 6	70	Stainless steel	0,35	25	6	20000 rpm	20	358336
22 x 6	70	Steel	0,35	25	8	20000 rpm	10	358339
22 x 6	70	Stainless steel	0,35	25	8	20000 rpm	10	358341

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Shaft in mm	Total length in mm	Fill material	Wire thickness in mm	Fill length in mm	Number of knots	Max. RPM	Packing unit/pcs.	Cat. number
30 x 6	72	Steel	0,35	25	12	20000 rpm	10	358344
30 x 6	72	Stainless steel	0,35	25	12	20000 rpm	10	358345

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de