Wheel brush, knotted wire

BR 600 Z







Product benefit

Wheel brush for pre- and post-processing of welding seams - For aggressive removal of scale, rust, slag - For heavy brushing and deburring work

Materials

Stainless steel	●
Steel	●

Applications

- Plant engineering
- Apparatus and container manufacturing
- Stainless steel processing industry
- Railing construction
- Metal construction
- Steel construction
- Locksmith's shop

Diameter x Width x Bore in mm	holding device	Fill material	Wire thickness in mm	Fill length in mm	Number of knots	Max. RPM	Packing unit/pcs.	Cat. number
115 x 14 x 22,23		Steel	0,50	22	20	12500 rpm	1	358311
115 x 14 x 22,23		Stainless steel	0,50	22	20	12500 rpm	1	358342
115 x 14	thread M14	Steel	0,50	22	22	12500 rpm	1	370717
115 x 14	thread M14	Stainless steel	0,50	22	22	12500 rpm	1	370718

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Width x Bore in mm	holding device	Fill material	Wire thickness in mm	Fill length in mm	Number of knots	Max. RPM	Packing unit/pcs.	Cat. number
125 x 14 x 22,23		Steel	0,50	22	24	12500 rpm	1	358312
125 x 14 x 22,23		Stainless steel	0,50	22	24	12500 rpm	1	358343
125 x 14	thread M14	Steel	0,50	22	26	12500 rpm	1	370719
178 x 14 x 22,23		Steel	0,50	42	30	9000 rpm	1	358313
178 x 14 x 22,23		Stainless steel	0,50	42	30	9000 rpm	1	363720
178 x 14	thread M14	Steel	0,50	39	36	9000 rpm	1	370720

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de